

QUAD OUTPUT ADJUSTABLE DC POWER SUPPLY

M10-QP SERIES



Features

- **Output off function**
- **Quad independent DC outputs**
 - Independent, series and parallel variety output
 - Constant voltage and constant current
 - Low ripple and noise
 - Plastic panel
- Four LED displays with 3 digits, selectable for two sets output voltage and current display simultaneously



M10-QP305E

Specifications

- Line regulation: CV $1 \times 10^{-4} + 3\text{mV}$ CC $2 \times 10^{-3} + 3\text{mA}$
- Load regulation: CV $1 \times 10^{-4} + 4\text{mV}$ CC $2 \times 10^{-3} + 5\text{mA}$
- Ripple & noise: CV 1mV rms CC 3mA rms
- Display accuracy: $\pm 0.5\% \text{Rdg} + 2 \text{digits}$
- Input voltage: 110~127VAC $\pm 10\%$, 220~240 $\pm 10\%$ Switchable

Model	Independent Output	Series Output	Parallel Output	Dimensions (W×H×D)	Weight (kg)
M10-QP303E	CH1 0~30V/0~3A	CH1+CH2	CH1//CH2	260 × 160 × 310mm	8.5
	CH2 0~30V/0~3A	0~60V/0~3A	0~30V/0~6A		
	CH3 3~6.5V/3A	CH3 3~6.5V/3A	CH3 3~6.5V/3A		
	CH4 8~15V/1A	CH4 8~15V/1A	CH4 8~15V/1A		
M10-QP305E	CH1 0~30V/0~5A	CH1+CH2	CH1//CH2	260 × 160 × 310mm	9.5
	CH2 0~30V/0~5A	0~60V/0~5A	0~30V/0~10A		
	CH3 3~6.5V/3A	CH3 3~6.5V/3A	CH3 3~6.5V/3A		
	CH4 8~15V/1A	CH4 8~15V/1A	CH4 8~15V/1A		