

# TRIPLE OUTPUT ADJUSTABLE DC POWER SUPPLY

M10-QR SERIES



## Features

- . Output off function
- . Triple independent DC outputs. Two adjustable and one fixed output
- . Independent, series and parallel variety output
- . Constant voltage and constant current
- . Low ripple and noise
- . Four LED displays with 3 digits, selectable for two sets output voltage and current display simultaneously
- . 16 hours continuous output with full load
- . Auto tracking output



M10-QR305

## Specifications

- .Line regulation: CV  $1 \times 10^{-4} + 3\text{mV}$  CC  $2 \times 10^{-3} + 3\text{mA}$
- .Load regulation: CV  $1 \times 10^{-4} + 4\text{mV}$  CC  $2 \times 10^{-3} + 5\text{mA}$
- .Ripple & noise: CV 1mV rms CC 3mA rms
- .Display accuracy:  $\pm 0.5\% \text{Rdg} + 2\text{digits}$
- .Input voltage: 110~127VAC  $\pm 10\%$ , 220~240  $\pm 10\%$  Switchable

Model	Independent Output	Series Output	Parallel Output	Dimensions (W×H×D)	Weight (kg)
M10-QR302	CH1 0~30V/0~2A CH2 0~30V/0~2A CH3 1A/5V	CH1+CH2 0~60V/0~2A	CH1//CH2 0~30V/0~4A	250×135×300 mm	8.2
M10-QR303	CH1 0~30V/0~3A CH2 0~30V/0~3A CH3 1A/5V	CH1+CH2 0~60V/0~3A	CH1//CH2 0~30V/0~6A	250×135×300 mm	8.2
M10-QR305	CH1 0~30V/0~5A CH2 0~30V/0~5A CH3 1A/5V	CH1+CH2 0~60V/0~5A	CH1//CH2 0~30V/0~10A	250×135×300 mm	9

POWER SUPPLY

TEST INSTRUMENT

EDU. INSTRUMENT

METER

ACCESSORY