

LED Light Meter

TM-201L



TM-205AL



TM-209



TM-209M



According to JIS C 1609:1993 and CNS 5119 general A class Specifications.

Features & Specifications

Models	TM-201L	TM-205AL	TM-209	TM-209M
Max hold	●			
Max / Min		●		
Max / Avg/ Min Hold			●	●
Zero adj.	●	●	●	●
Read memory			●	●
Auto-Power Off		●	●	●
Disable Auto Power Off			●	●
Auto ranging		●	●	●
Manual ranging	●	●		
Measuring lights source	LED white light and all visible light.			6 LED lights source and all visible light measuring: L0➡ Standard light source A : 1.00. L1➡ LED white day light L2➡ LED RED light L3➡ LED AMBER(YELLOW) light L4➡ LED GREEN light L5➡ LED BLUE light L6➡ LED PURPLE light L7~ L9➡Default Standard light source A
Display	2000 count, maximum display 1999	maximum display 1999	4000 count, maximum display 3999	
Measuring Range	200~200000 Lux 20~20000 FC	20~200,000Lux 20~20,0000FC	40,400,4000, 40000,400000 Lux 40,400,4000,40000 Footcandles	
Accuracy	±3% (Calibrated to standard incandescent lamp 2856°K)			
	±8% other visible light source	±6% other visible light source		
Sensor	Silicon photodiode and filter			
Sampling Rate	2.5 times / second			
Battery life	About 200 hours			
Weight	250 g (include battery)			
Dimensions(LXWXH)	TM-201L/209/209MMeter:130 x 55 x 38mm, TM-205AL Meter:140 x 65 x 37.5mm Sensor: 80 x 55 x 25mm ; cable of light sensor: Approx. 1.5M			